

MATERIAL SAFETY DATA SHEET



HAZARD RATINGS HMIS	
Health	0
Flammability	1
Reactivity	0
PPE	X

1 CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product HM4315
MSDS Name H/M 4315
CAS # Mixture
Generic Description EVA Based Hot Melt Adhesive
Manufacturer BOSTIK FINDLEY, INC.
211 Boston Street
Middleton, MA 01949 USA

24 Hour Emergency Assistance
Phone: 1-800-227-0332

General Assistance
Phone: 1-978-777-0100

MSDS Assistance
Phone: 1-978-777-0100

2 COMPOSITION / INFORMATION ON INGREDIENTS

No hazardous ingredients as per 29 CFR 1910.1200.

3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Extended contact with this material may cause irritation to the skin, eyes, and mucous membranes. Contact with molten material will cause thermal burns. Primary Routes of Exposure: eyes, skin, and inhalation.

POTENTIAL HEALTH EFFECTS

Skin Contact: Molten material will produce burns to skin areas.

Eye Contact: May cause irritation with temporary redness with stinging and tearing.

Inhalation: Inhalation of hot mist may cause respiratory irritation.

Ingestion: Exposure is unlikely. This product can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

TARGET ORGANS

None known for product as a whole.

4 FIRST AID MEASURES

SKIN

If burned by contact with molten material, cool as quickly as possible with water. Do not remove material from skin. Keep affected area covered with cold, clean, wet compresses. Get medical attention immediately. See Notes to Physician.

EYE

If molten material contacts the eye, immediately flush with plenty of water for at least 15 minutes. Get medical attention immediately. See Notes to Physician.

MSDS Number	19077	Product	HM4315
Label Number	19077	NA = Not Available	ND = Not Determined

Date of preparation: 09/05/03

SECTION VIII EMPLOYEE PROTECTION

RESPIRATORY PROTECTION: None required with normal product use. If abraded, use of a dust filter respirator is recommended to prevent inhalation of fibers.

PROTECTIVE CLOTHING: Wear safety glasses, cotton work gloves.

ADDITIONAL PROTECTIVE MEASURES: Not applicable.

SECTION IX ENVIRONMENTAL PROTECTION

SPILL OR LEAK PROCEDURES: Not applicable as product is a solid.

WASTE DISPOSAL: Observe all Federal, State and local regulations regarding proper disposal.

SECTION X ADDITIONAL PRECAUTIONS

Prevent contact with fire, prevent "job-site" damage.

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

Product: Red Rosin Paper

Effective: August 13, 2001
Supercedes: New

Page 1 of 2

SECTION I

Manufacturer's Name
Fortifiber Corporation

Emergency Telephone No.
508-222-3500

Address: 55 Starkey Ave., Attleboro, MA 02703

Chemical Name & Synonyms
N/A

Trade Name & Synonyms
Red Rosin Paper

Chemical Family
Paper

Formula
N/A

SECTION II - HAZARDOUS INGREDIENTS

This product is exempt from the OSHA Hazard Communication Regulations in 29 CFR 1910.1200 (b)(5)(iii), 29 CFR 1910.1200 (b)(5)(iv), and 29 CFR 1910.1200 (b)(6)(v) in that the wood and wood products exemption has been interpreted to include paper.

SECTION III - PHYSICAL DATA

Boiling Point (°F.)
N/A

Specific Gravity (Water=1)
> 1.0

Vapor Pressure (mmHg.)
N/A

Percent Volatile by Volume (%)
N/A

Vapor Density (Air=1)
N/A

Evaporation Rate(Butyl Acetate=1)
N/A

Solubility in Water Negligible

Appearance & Odor Pink to red colored paper

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point >450°F Method Cleveland Cup

Flammable Limits N/A LeI N/A/VeI N/A

Extinguishing Media Water spray, CO₂ fog or foam, Dry Chemical

Special Fire Fighting Procedures None

Unusual Fire and Explosion Hazards None